

ENQUIRY FORM

COMPANY		NAME AND SURNAME	
OFFER REFER.		INSTALLATION ADDRESS	


MODEL



CAPACITY	300	1000	2000	3000	4000	5000	300	500	1500
	600	1500	2500				1000	2000	
ATTENDANT ON BOARD	SPB			SPB			SPB		
REVERSE TROLLEY	"R" Version								

DIMENSIONS AND GENERAL FEATURES OF THE SYSTEM

TRAVEL	mm	ACCESS	
LENGHT*	mm	STOPS	
DEPTH*	mm	SERVICES	



ACCESS POSITION	
A	On levels _____
B	On levels _____
C	On levels _____

*measurements refer to: Shaft Platform

SHAFT

REINFORCED CONCRETE	Made of reinforced concrete class C20/25		
METAL STRUCTURE	Supplied by UpDinamic	Made by the Customer	
	Indoor	Outdoor	

OUTFITTINGS

STANDARD OUTFITTING	Standard Updinamic with simple platform		
PARAPETS	Made of blind painted steel panels RAL9006		
	H.1100mm	H.1800mm	
CABIN	Made of steel painted walls and ceiling RAL9006		
	H.2100mm	H.2300mm	

SURFACES

STANDARD FINISH	Standard painted steel, structures in RAL7016 and panels in RAL9006		
ZINC PRIMER**	Flooring	Panels/ Parapets	Cabin
INOX 304	Flooring	Panels/ Parapets	Cabin
INOX 316	Flooring	Panels/ Parapets	Cabin

**Surfaces treated with antacid zinc primer and powder coating

